

HC-49U/S Crystal

Part Number Guide

T-M-FF.FFFM-LC-FTFS-OT-ESR

T (Type型号): S=HC-49S, 2 Leads with height of 3.38mm Max
 S2=HC-49S, 2 Leads with height of 2.8mm Max
 S3=HC-49S, 2 Leads with height of 2.5mm Max
 SB=HC-49S, 3 Leads with height of 3.38mm Max
 SB2=HC-49S, 3 Leads with height of 2.8mm Max
 SB3=HC-49S, 3 Leads with height of 2.5mm Max

M (Mode of Operation 振荡模式): F=Fundamental T=Third Overtone, etc

F (Frequency 标称频率): Normal - 5 digitals of Frequency, e.g. 8.0000M, 12.000M
 Special - All digitals of Frequency, e.g. 13.225625M

LC (Load Capacitance 负载电容): 20=20pf 00=series, etc

FT (Frequency Tolerance 调整频差): 30=±30 ppm, etc

FS (Frequency Stability 温度频差): 50=±50 ppm, etc


OT (Operating Temperature 工作温度): 1060=-10°C to +60°C 4085=-40°C to +85°C, etc

ESR (Equivalent Series Resistance 等效阻抗)

A (Automotive 车载应用)

Electrical Specifications 电气参数



Item 项目	Spec 规格	Condition 条件	
Frequency Range 频率范围	3.2768MHz~40.68MHz	For further questions regarding specifications, please feel free to contact us. 对于超出标准的规格, 请联系我们	
Operating Temperature 工作温度	-40~85°C, -55~125°C		
Drive Level 激励功率	100 μw max	It is recommended to use 1 μw~100 μw 推荐1 μw~100 μw	
Load Capacitance 负载电容	7pF~∞	For further questions regarding specifications, please feel free to contact us. 对于超出标准的规格, 请联系我们	
Frequency Tolerance 调整频差	±30ppm Standard (±10~±50ppm Available)		
Frequency Stability 温度频差	±30ppm@-40~85°C ±50ppm@-55~125°C		
Aging 老化率	±5ppm		
Storage Temperature 储存温度	-55~125°C		
ESR 等效阻抗 (Ω)	3.2768MHz ≤ F0 < 4MHz		150 Ω
	4MHz ≤ F0 < 5MHz		120 Ω
	5MHz ≤ F0 < 6MHz	100 Ω	
	6MHz ≤ F0 < 7MHz	80 Ω	
	7MHz ≤ F0 < 10MHz	60 Ω	
	10MHz ≤ F0 < 14MHz	50 Ω	
	14MHz ≤ F0 < 20MHz	40 Ω	
	20MHz ≤ F0 < 40.68MHz	30 Ω	



Pb Free RoHS Compliant

Mechanical Dimensions 外型尺寸

S: TWO LEADS (两引线) UNIT (单位): mm (毫米)



SB: THREE LEADS (三引线) UNIT (单位): mm (毫米)

